

CAPNOCHECK® PLUS CAPNOGRAPH

SPECIFICATIONS:

Displays & Indicators:

Display	Vacuum fluorescent
Indicators	Alarm, Charge, Silenced
Displayed Trends	Graphical display, user selectable sample rate, user-selectable trend up to 16 hr. display at 12 sec. sample rate, up to 10 hr. display at 4 sec. sample rate
Displayed Waveforms	Selectable CO ₂ or CO ₂ /Plethysmogram Waveform

Alarms:

Physiological	Adjustable volume, user-selectable high and low limits for all displayed parameters Screen indicators for each parameter
System Silence	Adjustable volume Temporary 2 min. or indefinite LED indicator

Flow Rate:

150 ml/min, \pm /-20

CO₂:

Measurement	Non-dispersive IR absorption
Measurement Range	0-10% CO ₂
Units	User-selectable: mmHg, Vol. %, kPa
Display Range	0-100 mmHg or 0-10.0% CO ₂ or 0-13.3 kPa
Accuracy	\pm 2 mmHg; \pm 0.3%; \pm 0.3 kPa, or 4% of reading, whichever is greater (0-10%CO ₂)
Resolution	1 mmHg; 0.1%; 0.1 kPa
Calibration	2 point Cal
N ₂ O-Compensation	User-selectable 40% (default = OFF)
Rise Time	360ms (average)
Averaging	4-breath average, or breath-by-breath, user selectable

Respiration Rate:

Range	0-150 bpm
Averaging	4-breath average
Accuracy	\pm 1bpm

SpO₂ (Optional):

Range	0-100% functional SpO ₂
Accuracy	\pm 2% at 70-100%; \pm 3% at 50-69%
Averaging	4, 8, or 16-beat, user selectable (default: 8)

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
Please read the Instructions for Use supplied with the product for detailed instructions, warnings, and cautions.

Pulse Rate (Optional):

Range	30-250 bpm
Accuracy	\pm 2% at 30-250 bpm
Averaging	8 or 16 seconds, user selectable
Pulse Tone	Pitch corresponds to SpO ₂ value Volume adjustable or OFF

FIO₂ (Optional):

Range	0-100%
Accuracy	\pm 2%
Response Time	< 10 seconds to 90%
Drift	< 2% full scale per month

Power:

AC Charger Input	115V~, 60 Hz [Optional] 100V~, 50 Hz [Optional] 230V~, 50/60 Hz
Battery	Nickel Cadmium battery, 6 VDC, internal rechargeable, not user replaceable, fully charged continuous-use life 2 hours approximate, maximum full charge time 4 hours.

Serial Output:

RS232C	Tabular trends, patient data
--------	------------------------------

Analog Output:

Any three of: CO ₂ waveform, Plethysmogram, End Tidal CO ₂ , Respiration Rate, Inspired CO ₂ , % SpO ₂ , Pulse Rate Fractional Inspired Oxygen, 0V or 1V Cal Signal	
Range	0-1 VDC full scale

Physical:

Dimensions	3.5" H x 10.0" W x 5.5" D [8.9 cm H x 25.4cm W x 13.9cm D]
Weight	4.8 pounds [2.2 kg]

Environment:

Operating Temperature	32°F to 122°F (0°C to 50°C)
Storage Temperature	-40°F to 158°F [-40°C to 70°C]
Relative Humidity [non-condensing]	10-95% [storage] 15-95% [operating]

Standards:

EN60601-1, EN60601-1-1, UL 544, EN60601-1-2, CSA Std. C22.2 No. 125-1994

Regulatory Compliance:

510(k): K970209
ISO 9001/ISO 13485



Catalog Number:

9004 Capnocheck® Plus Capnograph
Available languages: English, German, French, Italian, Spanish, Portuguese